OC-12/STM-4 Trunk Modules for the Stinger® DSL Access Concentrator

This Stinger® trunk module offers higher transport speeds, up to 622 Mbps, along with the flexibility to meet a wide range of operating requirements efficiently and cost effectively. It gives you a choice of two high-speed fiber interfaces to the ATM core network, subtending capabilities for scalability and dual-port modules enabling redundancy. With the OC-12/STM-4 module installed, you can improve performance for sophisticated data applications. And compatibility with other Stinger® trunk modules allows you to support diverse services from a single chassis.

Applications

- High-capacity DSL aggregation
- APS support for increased reliability
- Support for lucrative, bandwidth-intensive services, such as video, multimedia and corporate data services
- Reliable bandwidth for premium services

Features

- **Transport speeds up to 622 Mbps**—Improves performance for high-value services, helping to keep customers satisfied.
- **Optical interface options**—Provides a choice of OC-12 or STM-4 technology to suit your requirements, with single-mode long-reach or intermediate-reach.
- **Intermediate-reach mode**—Supports Stinger® FS and FS+ chassis located up to 15 kilometers from the ATM core network.
- **Long-reach mode**—Extends support up to 40 kilometers from the ATM core network.
- **Subtending capabilities**—Allows multiple Stinger® FS and FS+ units to be cascaded for more efficient, cost-effective traffic aggregation.
- **Dual-port modules**— The OC12-ATM trunk module provides line redundancy by implementing linear 1+1 automatic protection switching (APS).
- **Compatibility**—Enables the OC-2/STM-4 trunk module to operate alongside other Stinger® trunk modules in the same chassis—to support diverse operating requirements.

Benefits

- **Enhanced revenue opportunities**—Take advantage of increased transport speeds to offer a full array of high-value services, including videoconferencing and broadcast TV.
- **Flexibility**—With this module's options for technology, reach, subtending and redundancy, it's easy to satisfy your unique operating requirements.
- **Increased efficiency**—Flexible configuration capabilities allow you to streamline operations and cut costs.
- **Scalability**—Cascade multiple units for cost-effective use of network resources.
- **Improved performance**—Keep customers satisfied with higher speeds and reliability.

Lucent Technologies
Bell Labs Innovations

Technical Specifications

1. **Availability**
   Only available for the Stinger® FS and FS+ chassis equipped with version 2 or later control modules

2. **Dimensions**
   Height: 15 inches (38.1 cm)
   Width: 1.06 inches (2.69 cm)
   Depth: 5 inches (12.7 cm)

3. **Weight**
   1.5 lbs. (0.68 kg)

4. **Operating Requirements**
   Temperatures:
   FS+/FS version: 32°–131° F (0° to 55° C)
   Relative humidity:
   0–90% (noncondensing)
   Operating altitude:
   Up to 13,123 ft. (4,000 m)

5. **Electromagnetic Compliance**
   Agency approvals
   Electromagnetic Emissions Certifications: FCC Part 15 Class A, and CISPR Class A
   EN55022 Class A
   AS/NZS3548 Class A

6. **Interface standards**
   OC-12c:
   ANSI T1.105
   ANSI T1.106
   STM-4:
   ITU G.957 (optical)
   ITU G.709 (optical)

7. **Physical connectors**
   Industry-standard LC connectors

8. **Physical interfaces**
   Two UNI 3.0/3.1 cell-bearing OC-12c/ STM-4 622-Mbps ports (optical)

9. **Maximum modules**
   Fully supports one per chassis

10. **Other OC-12 standards**
    ATM Forum UNI 3.0/3.1
    ANSI T1M1.3/92-005R1
    Telcordia® TR-NWT-001112
    Telcordia® GR-253-CORE
    RFC 1595

11. **Other STM standards**
    ATM Forum UNI 3.0/3.1
    ANSI T1M1.3/92-005R1
    Telcordia® GR-253-CORE
    RFC 1595

12. **Certifications**
    Telcordia GR-63-CORE
    (NEBS™ Level 1-3)
    Telcordia GR-1089-CORE
    EN/IEC 60950

13. **Power Requirements**
    17 W

14. **Optical Specifications**
    Intermediate-Reach:
    Up to 15 kilometers (9.3 miles).
    TX power: -15 decibels referred to 1 milliwatt to -8dBm
    RX Sensitivity: -8dBm to -28dBm
    Nominal wavelength: 1310 nanometers
    Long-Reach:
    Up to 40 kilometers (24.9 miles)
    TX power: -2 decibels referred to 1 milliwatt to -3dBm
    RX Sensitivity: -8dBm, -28dBm
    Nominal wavelength: 1310 nanometers

15. **Model Numbers**
    STGR-TM-OC12 Two-port trunk module with OC12/STM-4 interface (single mode, intermediate reach) for operation at 622Mbps per port over single-mode fiber, at distances up to 15km (9.3 miles)
    STGR-TM-OC12-L Two-port trunk module with OC12/STM-4 interface (single mode, long reach) for operation at 622Mbps per port over single-mode fiber, at distances up to 40km (24.9 miles)

To learn more, contact your Lucent Technologies representative, authorized reseller, or sales agent. Or, visit our Web site. www.lucent.com

Specifications subject to change without notice.

This document is for planning purposes only, and is not intended to create, modify or supplement any Lucent Technologies specifications or warranties relating to these products or services. Information and/or technical specifications supplied within this document do not waive (directly or indirectly) any rights or licenses – including but not limited to patents or other protective rights – of Lucent Technologies or others.

Stinger is a registered trademark of Lucent Technologies Inc.

NEBS is a trademark, and Telcordia is a registered trademark of Telcordia Technologies.

©2004 Lucent Technologies, Inc.
Printed in the U.S.A.

OC12 v1.0304

Lucent Technologies
Bell Labs Innovations